



Duratec™ SFB

Made from carbon steel with a flexible back, Duratec™ SFB is ideal for economical cutting on easy-to-machine ferrous or non ferrous metal and wood.

Features:

- ▶ Flexible carbon steel back.
- ▶ Wide range of widths, thickness and pitches.

Benefits:

- ▶ Ability to be run at higher band speeds.
- ▶ Economical general purpose cutting.
- ▶ Ideal for both contour & straight cutting.

Applications:

- ▶ Wood, plastics.
- ▶ Non ferrous foundry materials.
- ▶ Low alloy and nonferrous metals.
- ▶ Furniture, composition board.
- ▶ Light vertical and horizontal machines.

SOLID



TUBULAR



STRUCTURAL



BUNDLE



■ Primary Application
■ Secondary Application

Duratec™ SFB (formerly known as Super Flex-Back)

Blade Width x Thickness		Tooth Pitch							
mm	Inch	3	4	6	8	10	14	18	24
3 x 0.65	1/8 x .025						FB-R	FB-R	FB-R
5 x 0.65	3/16 x .025			FB-S		FB-R	FB-R	FB-R	FB-R
6 x 0.35	1/4 x .014			FB-S		FB-R	FB-R		
6 x 0.65	1/4 x .025		FB-S / FB-H	FB-S / FB-H		FB-R	FB-R	FB-R	FB-R
8 x 0.65	5/16 x .025					FB-R	FB-R	FB-R	
10 x 0.35	3/8 x .014			FB-S	FB-R		FB-R		
10 x 0.65	3/8 x .025	FB-S / FB-H	FB-S / FB-H	FB-S / FB-H	FB-S / FB-H	FB-R	FB-R	FB-R	FB-R
13 x 0.35	1/2 x .014						FB-R		
13 x 0.65	1/2 x .025	FB-S / FB-H	FB-S / FB-H	FB-R / FB-S / FB-H	FB-R	FB-R	FB-R	FB-R	FB-R
16 x 0.80	5/8 x .032	FB-S	FB-S	FB-S	FB-R	FB-R	FB-R	FB-R	
19 x 0.80	3/4 x .032	FB-S / FB-H	FB-S	FB-R	FB-R	FB-R	FB-R	FB-R	
27 x 0.90	1 x .035	FB-S / FB-H	FB-R / FB-S	FB-R	FB-R	FB-R	FB-R		

H - Hook Tooth Shape: S - Skip Tooth Shape: R - Regular Tooth Shape: All FB Blades Are Raker Tooth Set Apart From 3mm x 0.65mm x 24R - Wavy Tooth Set