

Analogue Bore Gauging

Features

Standard: DIN 863

- Range 2-300mm
- 2-6mm 2 point / 6-300mm 3 point measurement
- Tungsten carbide contact points above 12.5mm
- Traceable certificates supplied as standard with all micrometers and setting rings
- Blind bore measurement from 2 - 6mm and above 12.5mm diameter
- Micrometer head fitted with a ratchet for constant gauging pressure
- Supplied in robust fitted case
- Extensions available above 6mm for deep hole measurement
- Price includes setting ring
- Available as individual instruments or boxed sets



ANALOGUE BORE GAUGING

Code No	Range	Accuracy	Depth
MW-225	2-2.5mm	0.004mm	9mm
MW-253	2.5-3mm	0.004mm	9mm
MW-34	3-4mm	0.004mm	12mm
MW-45	4-5mm	0.004mm	18mm
MW-56	5-6mm	0.004mm	18mm
MW-68	6-8mm	0.004mm	58mm
MW-810	8-10mm	0.004mm	58mm
MW-10125	10-12.5mm	0.004mm	58mm
MW-12516	12.5-16mm	0.004mm	62mm
MW-1620	16-20mm	0.004mm	62mm
MW-2025	20-25mm	0.004mm	66mm
MW-2535	25-35mm	0.004mm	66mm
MW-3550	35-50mm	0.004mm	80mm
MW-5065	50-65mm	0.005mm	80mm
MW-6580	65-80mm	0.005mm	80mm
MW-80100	80-100mm	0.005mm	100mm
MW-100125	100-125mm	0.006mm	115mm
MW-125150	125-150mm	0.006mm	115mm
MW-150175	150-175mm	0.007mm	115mm
MW-175200	175-200mm	0.007mm	115mm
MW-200225	200-225mm	0.008mm	118mm
MW-225250	225-250mm	0.008mm	118mm
MW-250275	250-275mm	0.009mm	118mm
MW-275300	275-300mm	0.009mm	118mm

BOXED SETS

Code No	Range
MWS-23	2-3mm
MWS-36	3-6mm
MWS-610	6-10mm
MWS-1020	10-20mm
MWS-2050	20-50mm
MWS-50100	50-100mm
MWS-100150	100-150mm
MWS-150200	150-200mm