

Ultrasonic Thickness Gauge IPX-251H

Handheld ultrasonic thickness gauge for thickness measurement of various materials with large memory and USB output

Features

- Pocket size, easy to operate
- Automatic probe Zero calibration
- Automatic probe identification
- Display resolution: 0.01mm/ 0.1mm selectable
- Measuring range: 0.65 – 400 mm (range depends on probe-material combination)
- Suitable for various materials such as steel, stainless steel, aluminium, glass, polystyrene, polyethylene
- Limit setting: With Low-High Indication and alarm
- Memory: 5000 readings with location number
- Data output: USB to PC
- Temp. of material: -15°C - 55°C (with standard probe)
- Power Supply: AAA dry cell 1.5 V (2 Pcs) (NOT SUPPLIED)



OPTIONAL PROBES

Freq.	Meas. Range (mm)	Diam Ø	Temp. °C
5.0 MHz	0.8 - 400	11.0	< 60°C
5.0 MHz	3.0 - 200	15.2	< 350°C
7.5 MHz	0.7 - 50	9.0	< 60°C
10.0 MHz	0.65 - 20	6.0	< 60°C
2.0 MHz	2.0 - 400	17.0	< 60°C

TECHNICAL SPECIFICATION

Display	128 x 64 with backlight
Measuring range	0.65-400mm (depends on probe-material combination)
Velocity rate	1000 – 9999m/s 9 material velocities stored for selection, or input velocity manually
Resolution	0.1mm/ 0.01mm selectable
Measuring units	mm/inch
Accuracy	±0.04mm (when thickness<9.99mm) ± (0.1% thickness+0.04) mm (when thickness =10~99.9mm) ±0.3% thickness mm (when thickness>100mm)
Average mode:	2~9 times average measurement
Limit setting:	Low-High indication and alarm
Memory:	5000 readings with location number
Data output:	USB to PC
Surface temperature:	-15°C to +350°C
Battery Indicator:	Low battery indicator
Power supply:	2 Pcs AAA dry cell (NOT SUPPLIED)
Battery lifework:	48 Hours continuously (without backlight)
Dimensions:	115 x 64 x 27mm
Weight:	220g

Standard Delivery

- Main unit
- Standard 5MHZ transducer
- Built-in calibration block 4mm
- Software + cable
- Manual
- INSPEX certificate
- Carrying case