

Dial Test Indicator

Features

Standard: DIN2270

- Automatic reversal of measuring direction
- High precision fully jewelled bearings
- Rotating dial
- Two dovetail clamps
- Carbide points
- Long range - twice the range of most indicators (422 series only)



420 Series



421 Series



422 Series

DIAL TEST INDICATOR 420 SERIES

Code No	Range	Graduation	Dial Reading	Dial Diameter	Dial Colour	Feeler Length
MW420-03	0.8mm	0.01mm	0-40-0	30mm	white	12mm
MW420-03I	0.030"	0.0005"	0-15-0	1"	white	1/2"
MW420-04	0.8mm	0.01mm	0-40-0	37mm	white	12mm
MW420-04I	0.030"	0.0005"	0-15-0	1 1/2"	white	1/2"

DIAL TEST INDICATOR 421 SERIES

Code No	Range	Graduation	Dial Reading	Dial Diameter	Dial Colour	Feeler Length
MW421-01	0.2mm	0.002mm	0-100-0	30mm	white	12mm
MW421-01I	0.008"	0.0001"	0-4-0	1"	white	1/2"
MW421-02	0.2mm	0.002mm	0-100-0	37mm	white	12mm
MW421-02I	0.008"	0.0001"	0-4-0	1 1/2"	white	1/2"

DIAL TEST INDICATOR 422 SERIES

Code No	Range	Graduation	Dial Reading	Dial Diameter	Dial Colour	Feeler Length
MW422-01	1.6mm	0.01mm	0-40-0	37mm	white	12mm
MW422-01I	0.060"	0.0005"	0-15-0	1 1/2"	white	1/2"

Dial Test Indicator Accessories



DIAL TEST INDICATOR: ACCESSORIES

Code No	Description
MW-Z400/10	Universal Holder
MW-Z400/12	Contact point 12mm length, 1mm steel ball
MW-Z400/13	Contact point 12mm length, 2mm carbide ball
MW-Z400/14	Contact point 12mm length, 3mm carbide ball
MW-Z400/16	Contact point 1/2" length, 0.040" steel ball
MW-Z400/17	Contact point 1/2" length, 0.080" carbide ball
MW-Z400/18	Contact point 1/2" length, 0.120" carbide ball
MW-Z400/20	Dovetail stem 4mm clamping diameter
MW-Z400/22	Dovetail stem 8mm clamping diameter